EROSION CONTROL MATTING GENERAL NOTES:

- 1. STRIPS OF MATTING SHALL BE INSTALLED PARALLEL TO THE DIRECTION OF FLOW OVER THE SURFACE WHICH IS TO BE PROTECTED.
- 2. THE UP-CHANNEL END OF THE MATTING SHALL BE BURIED IN A TRENCH MEASURING 6 INCHES DEEP AND 6 INCHES WIDE FOR THE ENTIRE WIDTH OF THE END. THE SOIL SHALL BE BACKFILLED INTO THE TRENCH AND TAMPED FIRMLY. STAPLES SHALL BE PLACED EVERY 12 INCHES ALONG THE END OF THE MATTING.
- 3. EDGES OF ADJACENT STRIPS OF MATTING SHALL BE OVERLAPPED A MINIMUM OF 4 INCHES AND SHALL BE STAPLED EVERY 3 FEET ALONG THE OVERLAP.
- 4. WHEN JOINING STRIPS OF MATTING END TO END, A TRENCH SIMILAR TO THE ONE DUG AT THE BEGINNING OF THE ORIGINAL STRIP SHALL BE DUG WITH THE UP-CHANNEL END OF THE NEW STRIP BEING PLACED IN A LIKE MANNER IN THE TRENCH AS THE BEGINNING END OF THE ORIGINAL STRIP. THE END OF THE STRIP BEING FOLDED UNDER AT LEAST 12 INCHES. STAPLES SHALL BE INSTALLED AT 12 INCH INTERVALS ALONG THE WIDTH OF THE STRIP NOT MORE THAN 6 INCHES FROM THE TRENCH.
- 5. IN SITUATIONS WHERE ERODIBLE SOILS, STEEP SLOPES OR HIGH VELOCITY FLOWS ARE ENCOUNTERED, A FOLD OF THE MATTING SHALL BE INSERTED INTO A 6 INCH TRENCH AND TAMPED FIRMLY. STAPLES SHALL BE INSTALLED AT 12 INCH INTERVALS ALONG THE TRENCH.
- 6. STAPLES FOR ANCHORING SOIL STABILIZING MATERIALS SHALL BE MADE OF 10 GAUGE WIRE OR HEAVIER. THEY SHALL BE 6 TO 10 INCHES IN LENGTH, WITH THE LONGER STAPLES BEING USED IN LOOSE OR UNSTABLE SOILS. THERE SHALL BE ONE STAPLE FOR EACH FOUR (4) SQUARE FEET OF MATTING TO ASSURE PROPER BONDING BETWEEN THE SOIL AND THE MAT MATERIAL.

| | _Ba | | NOV | 03 | | |
|---|-------------------|------------|------|----|---|---|
| 1 | Wichita Falls | DATE DRAWN | | | | |
| | | | | | | |
| | TEXAS | | | | | |
| | | | | | | |
| | Matting_Notes.dwg | NO. | DATE | | | |
| | ACAD DRAWING NAME | R | E | V | ı | - |

NOV 03 1160B-00 STANDARD DRAWING NO.

NO. DATE DESCRIPTION BY

R E V I S I O N S

CITY OF WICHITA FALLS, TX

EROSION CONTROL

MATTING NOTES

APPROVED

ENGINEER DATE

DISCLAIMER:

The use of this standard is governed by the City of Wichita Falls Engineering Department. No warranty of simmer is made by the City of Wichita Falls for any purpose whatsoever. The City of Wichita Falls assumes no ifor the conversion of this standard to other formats for incorrect results or damages resulting from its

of any kind responsibility s use.